

PLATINUM AUTOMATIC IGNITION

Q & A FOR THE PLATINUM AUTOMATIC IGNITION

IS THERE A STANDARD AND HIGH CAPACITY VERSION OF THE PLATINUM?

The Platinum Ignition is certified up to 680,000 BTUs. There is no need for a Standard and a High Capacity version.

WHAT IS THE VALVE AND INLET SIZING?

The Platinum has a 3/4" valve and gas inlet. It can be easily adapted to 1/2" manifolds.

■ IS THERE ANY DIFFERENCE BETWEEN THE NG AND LP VERSION OF THE IGNITION?

Yes, the Pilot Assembly on the Platinum is gas specific.

IS THIS A DUAL PILOT SYSTEM?

No, the Platinum Ignition is a single pilot system.

WILL THIS BE OFFERED WITH PILOT TUBE EXTENSIONS?

Yes. The Platinum comes with a two-foot pilot tube. The Pilot can be extended up to an additional 10 feet. We offer pilot tubing in one-foot increments.

WHAT IS THE PURPOSE OF THE LED INDICATOR LIGHT?

The LED Indictator light is for troubleshooting and diagnostic purposes and will pause between blinks to allow you to diagnose the issue being encountered.

WHAT IS THE VOLTAGE RANGE OF THE PLATINUM??

The Platinum operates at 24 volts. The transformer is wired for 120 volts. The transformer can be used with 240 or 480 volt outlets. This will require appropriate pig tail modifications to be made by the electrician on site.

DOES THE PLATINUM USE A STANDING PILOT?

Yes, the Platinum uses a standing pilot.



SUPERIOR PRODUCTS | MADE IN THE U.S.A. | OUTSTANDING CUSTOMER SERVICE

Visit us online at **Warming-Trends.com** for more information and pricing or call **303-346-2224** to speak with one of our Flame Specialists today.

VISIT US ONLINE TO LEARN MORE